



PLC-XP55

Desktop/installation LCD projector



- ◆ XGA resolution
- ◆ **4,500 ANSI lumens**
- ◆ **1100:1 contrast ratio**
- ◆ New PJ Net Plus system for network control, monitoring **and content delivery**
- ◆ Motorized zoom, focus & lens shift
- ◆ 2 data and 1 video input
- ◆ New design remote control with mouse control and laser pointer
- ◆ Vertical **and** horizontal electronic keystone correction
- ◆ Optional lenses with **new one touch change system**
- ◆ 'Lensless' version available – PLC-XP55L

Features in red indicate improvement over PLC-XP46

Model name	PLC-XP55
Panel type	1.3 inch TFT p-Si Type x 3
No. of pixels	2,359,296 (1024 x 768 x 3 panels)
Lamp	300W NSH
Brightness	4,500 ANSI Lumens
Contrast ratio	1,100:1
Uniformity	90% (corner to centre)
Up-down ratio/keystone correction	Lens shift 10:0~1:1, Digital keystone – U/D +/- 40°, L/R +/- 10°
Projection lens (standard)	F1.7 - 2.0, f =48.2 – 62.6mm
Throw ratio	1.8 – 2.35:1
Screen size	31" - 400" (100" at 3.6 – 4.7m)
Throw distance	1.4m – 14.7m
Zoom / focus	1:1.3 Motor driven
Input/output terminals	Input 1, computer: RGB (D-Sub15/DVI-D), Input 2, computer/video: RGBHV/Y,Pb/Cb,Pr/Cr (5x BNC) Input 3, video: Composite/S-video/Component (3xRCA) Audio input: Stereo mini-jack x 2, RCA x1
Control Port	Mouse Control, RS232C (USB, mini DIN 8 pin)
Computer compatibility	SXGA/XGA/SVGA/VGA/MAC
Colour systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Scanning frequency	H/V sync 15-100kHz, 50-100Hz, Dot clock 160 MHz
Sound output	2 x 2.0W Stereo
Fan Noise	35dBA (eco mode)
Voltage	100V-240V AC (auto voltage)
Dimensions (W x H x D)	319 x 168 x 429.5 mm
Weight	9.2 kg