

Portable Network LCD Projector



PLC-XP56

- ◆ **Portable: B4 Size 9.2kg (with Lens) 5000**
- ◆ **Component input for DVD and HDTV**
- ◆ **New PJ-Net Organizer Plus (Option)**
- ◆ **Progressive Scan System & 3D Digital Noise reduction for Video Image**
- ◆ **Digital Visual Interface (DVI with HDCP)**

Model name	PLC-XP56 Series
Panel	1.3inch TFT p-Si with Micro lens x 3
No. of pixels	2,359,296 (1024X768 dots)
Projection lamp	NSH 300W (With variable output, max 20%)
Brightness (typical)	5000 lumens
Uniformity	90% (corner to centre)
Contrast ratio	1200:1 (Lamp mode: Auto)
Up-Down ratio	Lens shift 10:0 ~ 1:1 Digital Keystone
Projection lens (Standard)	F 1.7 ~ 2.0, f=48.2 ~ 62.6mm Option Lens available
Screen Size	31"~400" (100" at 3.6~4.7m)
Throw distance	1.4m~14.7m
Zoom / Focus	1:1.3 Motor driven Bayonet Lens Mount system
Option Lens	Short Fixed, Short Zoom, Long Zoom and Ultra Long Zoom
Signal Terminal	Input 1: RGB(D-Sub15) IN / Motor Out : DVI-D Stereo IN/OUT (mini jack) Input 2: RGBHV, Y,Pb/Cb,Pr/Cr, Composite (BNC) : Stereo (mini jack) Input 3: Composite (RCA)/S-Video (mini DIN4)/ : Y,Pb/Cb,Pr/Cr(RCAx3), Stereo(RCAx2)
Control Port	Mouse Control, RS232C (USB, mini DIN8pin) Wired Remote control (mini jack)
Computer compatibility	SXGA/XGA/SVGA/VGA/MAC
Color systems	PAL / SECAM / NTSC / ? NTSC4.43 / PAL-M/N
Scanning frequency	H/V sync ~ 100kHz, ~ 100Hz Dot clock 180 MHz
Sound output	2.0W+2.0W
Fan Noise	35dBA (eco mode)
Voltage	100V-240V AC (auto voltage)
Dimensions(W x H x D)	319 x 168 x 429.5mm
Weight	9.2kg (with Lens) / 7.9kg (without Lens)